



BY BOUNDLESS TECHNOLOGIES

ADD S 4000/260 Video Display Terminal

Wyse 50, 50+ and 60 VDT
emulation set

Best UNIX compatibility
and Video performance in a
14" monochrome Terminal

High reliability backed by
our 3 year warranty

Designed and manufactured
in the USA



The ADDS 4000/260 has advanced data access, data manipulation and display features, including cut and paste and dual host/dual session capabilities. The terminal features selectable refresh rates up to 100Hz for clear, flicker free viewing and an ISO 9241.3 compliant mode to reduce operator eye strain. Bezel to bezel over scan is also available up to 82 Hz.

The ADDS 4000/260 emulation set includes the Wyse WY-50/50+, WY-60, DEC VT-100, VT-220, VT 320 and the ADDS Viewpoint and PC-Term. The ADDS 4000/260 is an ideal solution for customers using Wyse display terminals in legacy applications. As a SCO developer, you can count on the ADDS 4000/260 to function properly in the SCO environment.

Built in the Boundless "JIT" manufacturing facility on Long Island allows rapid delivery of any terminal in any configuration. You can select the ADDS 4000/260 of your choice in any phosphor color with any keyboard with the assurance that your order will be delivered quickly. Boundless backs its ADDS 4000/260 with a money back guarantee and a 3 year warranty.

Boundless Technologies 1-800-231-5445



BY BOUNDLESS TECHNOLOGIES

ADD5 4000/260 Video Display Terminal

Display Features:

- ◇ 14" Flat face, reduced glare, high resolution screen
- ◇ Bezel to Bezel overscan
- ◇ 60, 71, 82 and 100 hz selectable refresh rates for clear flicker free viewing
- ◇ Choice of Green, Amber or White phosphor
- ◇ 26,30, or 52 lines with top and/or bottom status lines
- ◇ 80 or 132 columns
- ◇ 10 pages of memory
- ◇ Variable-speed smooth scroll
- ◇ Double high, double wide characters
- ◇ Selectable screen saver

Desk Accessories:

- ◇ Calculator
- ◇ Calendar
- ◇ Clock
- ◇ ASCII Chart

Communications:

- ◇ Full/half duplex
- ◇ Local block
- ◇ Monitor mode
- ◇ Serial host Port
 - RS-232C main host
 - DTE, DB 25 female
 - up to 134.4k baud
- ◇ Serial Auxiliary Port
 - RS-232C second host/aux serial port
 - DCE, DB 25 female
 - Up to 38.4k baud
- ◇ Parallel Printer Port
 - IBM PC and Centronic compatible
- ◇ Optional Ethernet
 - 10BaseT TCP/IP
- ◇ Optional current loop

Dual Host Support

- ◇ Simultaneous connection and operation with two hosts
- ◇ Flexible display formats
- ◇ "Hot key" to alternate between hosts
- ◇ Printer port support for both hosts

Terminal Emulations:

- ◇ ADD5 Viewpoint
- ◇ VT 100
- ◇ VT 220
- ◇ VT 320
- ◇ Wyse 50
- ◇ Wyse 50+
- ◇ Wyse 60
- ◇ TVI 925
- ◇ SCO Console
- ◇ BBS ANSI
- ◇ AT 386

Regulatory Agencies:

- ◇ UL
- ◇ TUV-GS Mark
- ◇ FCC-B,
- ◇ CE
- ◇ MRP-II
- ◇ DHHS
- ◇ VCCI
- ◇ EPA Energy Star
- ◇ ISO 92413
- ◇ VCCI
- ◇ EN 55022 Class B
- ◇ VFG 243 B

Power:

- ◇ 90-264 Vac, 47-63 hz
- ◇ .20-.50a (max) operating
- ◇ EPA Energy Star ® "Sleep Mode"

Physical Characteristics

- ◇ L: 13.0", 33 cm
- ◇ W: 12.5", 31.8 cm
- ◇ H: 13.4", 34 cm
- ◇ Shipping weight: 29 lbs. , 13.2 kg

Boundless Technologies
1916 Route 96
Phelps, NY 14532
Phone (toll-free): 1-800-231-5445
Phone: 1-315-548-6189
Fax: 1-315-548-5100
www.boundless.com